

<b>HD684DP1(530-SP)</b>									
<b>DATE OF TESTED</b>		2019/6/30							
<b>APPLICABLE STANDARD</b>		QB/T 2476-2000							
<b>FINISH DESCRIPTION</b>		不锈钢抛光	POLISHED STAINLESS STEEL						
<b>mateiral grade</b>		chemical composition							
<b>REFERENCE</b>		<b>TENSILE STRENGTH Mpa</b>	<b>C</b>	<b>N1</b>	<b>Cr</b>	<b>Cu</b>	<b>N</b>	<b>Ti</b>	<b>Nb</b>
304SS		480	0.04	8.25	16.2	0.5	0.04	0.04	0.36
<b>DESCRIPTIONS OF GOODS</b>	<b>TEST ITEMS</b>	范围	STANDARD	<b>TEST DATA</b>		CONCLUSION			
				NO.1	NO.2				
Cylindrical lock	<b>SURFACE ROUGHNESS</b>	表面粗糙度	Ra≤6.3 μm	6.2	6.1	PASS			
	<b>LATCH LATERAL STATIC LOAD</b>	锁舌侧向静负荷	1500N	1500N	1500N	PASS			
	<b>Handle the axial tensile force</b>	执手轴向静拉力	1000N	1000N	1000N	PASS			
	<b>Handle the radial static load</b>	执手径向静载荷	800N	800N	800N	PASS			
	<b>Key unlocking torque</b>	钥匙开锁力矩	N.M≤1	1	1	PASS			
	<b>Pull out key</b>	钥匙拔出静拉力	N≤8	6	6.5	PASS			
<b>PICTURE</b>									
									