

| | | | | | | |
|------------------------------|--|----------------------|-----------|-----------|-----------|------------|
| HD657D(578ET-AB) | | | | | | |
| DATE OF TESTED | 2019/6/30 | | | | | |
| APPLICABLE STANDARD | QB/T 2476-2000 | | | | | |
| FINISH DESCRIPTION | 青古 | ANTIQUE BRASS | | | | |
| mateiral grade | | chemical composition | | | | |
| REFERENCE | TENSILE STRENGTH Mpa | PB | N1 | Cr | Cu | FE |
| BRASS | 480 | 2.0~2.8 | 1 | 0 | 59 | 0.5 |
| DESCRIPTIONS OF GOODS | TEST ITEMS | 范围 | STANDARD | TEST DATA | | CONCLUSION |
| | | | | NO.1 | NO.2 | |
| Cylindrical lock | SURFACE ROUGHNESS | 表面粗糙度 | Ra≤6.3 μm | 6.2 | 6.1 | PASS |
| | LATCH LATERAL STATIC LOAD | 锁舌侧向静负荷 | 1500N | 1500N | 1500N | PASS |
| | Handle the axial tensile force | 执手轴向静拉力 | 1000N | 1000N | 1000N | PASS |
| | Handle the radial static load | 执手径向静载荷 | 800N | 800N | 800N | PASS |
| | Key unlocking torque | 钥匙开锁力矩 | N.M≤1 | 1 | 1 | PASS |
| | Pull out key | 钥匙拔出静拉力 | N≤8 | 6 | 6.5 | PASS |
| PICTURE |  | | | | | |
| |  | | | | | |