

<b>HD651DST(588BK-SP)</b>									
<b>DATE OF TESTED</b>		2019/6/30							
<b>APPLICABLE STANDARD</b>		QB/T 2476-2000							
<b>FINISH DESCRIPTION</b>		不锈钢抛光	POLISHED STAINLESS STEEL						
<b>mateiral grade</b>		chemical composition							
<b>REFERENCE</b>		<b>TENSILE STRENGTH Mpa</b>	<b>C</b>	<b>SI</b>	<b>Cr</b>	<b>NI</b>	<b>S</b>	<b>P</b>	<b>Mn</b>
430ss		480	0.12	1	18	0.06	0.03	0.04	1
<b>DESCRIPTIONS OF GOODS</b>	<b>TEST ITEMS</b>	<b>范围</b>	<b>STANDARD</b>	<b>TEST DATA</b>		<b>CONCLUSION</b>			
				<b>NO.1</b>	<b>NO.2</b>				
Cylindrical lock	<b>SURFACE ROUGHNESS</b>	表面粗糙度	Ra≤6.3 μm	6.2	6.1	PASS			
	<b>LATCH LATERAL STATIC LOAD</b>	锁舌侧向静负荷	1500N	1500N	1500N	PASS			
	<b>Handle the axial tensile force</b>	执手轴向静拉力	1000N	1000N	1000N	PASS			
	<b>Handle the radial static load</b>	执手径向静载荷	800N	800N	800N	PASS			
	<b>Key unlocking torque</b>	钥匙开锁力矩	N.M≤1	1	1	PASS			
	<b>Pull out key</b>	钥匙拔出静拉力	N≤8	6	6.5	PASS			
<b>PICTURE</b>									
									