

SEDE CENTRAL DE ITW GLOBAL BRANDS

CAR CARE (OFICINA DE HOUSTON)

16200 Park Row Dr, suite 120 Houston, TX 77084

Ficha Técnica REPELENTE AL AGUA DE VIDRIO ORIGINAL RAIN-X®

DESCRIPCIÓN DEL PRODUCTO

Rain-X ® Glass Water Repellent trata la superficie del vidrio con una barrera invisible antiadherente y súper resbaladiza que repele la lluvia, el aguanieve y la nieve al contacto; mejorando drásticamente la visibilidad, la seguridad y la comodidad de conducción en todo tipo de clima.

CARACTERÍSTICAS Y BENEFICIOS

- La aplicación sencilla mejora la visibilidad, la seguridad y la comodidad de conducción en todo tipo de clima.

- Eficaz para repeler la lluvia, el aguanieve y la nieve.

DIRECCIONES

Limpiar y secar las superficies antes de tratar.

Aplicar en temperaturas superiores a 40 grados F.

Aplique Rain-X ® a un paño pequeño, doblado y seco.

Limpie sobre el vidrio exterior con un movimiento firme, circular y superpuesto.

Deje que el producto se seque; puede aparecer una ligera neblina

Vuelva a aplicar Rain-X ® para garantizar una cobertura completa y uniforme.

Elimine la neblina final con un paño seco o rociando agua sobre la neblina y limpiando con una toalla de papel.



3.5 oz 800002242



SAFETY DATA SHEET

Revision Date 02-Oct-2018

1. IDENTIFICATION

Product identifier Product Name

Rain-X Original Glass Treatment

Other means of identification Product Code Document

11890 SKU: 800002242, 800002243, 800002245, 800002250

Recommended use of the chemical and restrictions on useRecommended UseGlass Treatment Consumer UseUses advised againstNo information available

Details of the supplier of the safety data sheetSupplier AddressManufacturer AddressITW Global Brands16200 Park Row, Suite 120Houston, TX 77084Distributor

Manufactured and Distributed by:

May Also Be Distributed by: ITW Permatex Canada 101-2360 Bristol Circle Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

 Company Phone Number
 1-855-888-1988

 24-hour emergency phone number
 (CHEMTREC) 1-800-424-9300 or 1-703-527-3887 (U.S.)

 (RMPDC) 1-877-504-9352 (U.S.)
 (U.S.)

E-mail address: SDS@itwgb.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

Label elements

Emergency Overview

<u>Signal word</u> Danger

Causes serious eye irritation May cause drowsiness or dizziness Highly flammable liquid and vapor Version 5



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance(s)

Chemical Name	CAS No	Weight-%
ETHANOL	64-17-5	30 - 60
ACETONE	67-64-1	10 - 30
Isopropanol	67-63-0	10 - 30

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.

Ingestion	IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.			
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions protect themselves.			
Most important symptoms and effe	ects, both acute and delayed			
Symptoms	See section 2 for more information.			
Indication of any immediate medic	al attention and special treatment needed			
Note to physicians	Treat symptomatically.			
	5. FIRE-FIGHTING MEASURES			
Suitable extinguishing media Dry chemical, CO2, sand, earth, wate	r spray or regular foam			
Unsuitable extinguishing media CAUTION: All these products have a solid water stream as it may scatter a	very low flash point. Use of water spray when fighting fire may be inefficient Do not use a nd spread fire			
Specific hazards arising from the c Flammable vapors may be present ev	hemical ven at temperatures below the flash point.			
<u>Explosion data</u> Sensitivity to Mechanical Impact Sensitivity to Static Discharge	No information available. May be ignited by heat, sparks or flames.			
Protective equipment and precauti As in any fire, wear self-contained bre protective gear.	ons for firefighters eathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions, protective e	quipment and emergency procedures			
Personal precautions	Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes and inhalation of vapors. Use personal protective equipment as required. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).			
Environmental precautions				
Environmental precautions	See section 12 for additional ecological information.			
Methods and material for containm	ent and cleaning up			
Methods for containment	Prevent further leakage or spillage if safe to do so.			
Methods for cleaning up	Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.			
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.			
	7. HANDLING AND STORAGE			
Precautions for safe handling				

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep out of the reach of children.

Incompatible materials

None known

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ETHANOL	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m ³
		(vacated) TWA: 1900 mg/m ³	-
ACETONE	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	-
		(vacated) STEL: 2400 mg/m ³ The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
Isopropanol	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m ³
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³
		(vacated) STEL: 1225 mg/m ³	-

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses or goggles if splashing is likely to occur.
Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Clear Colorless
Odor	Alcohol

Odor threshold	No information available	
Property	Values	Remarks • Method
рН	1.5 - 2.5	
Melting point / freezing point	No information available	
Boiling point / boiling range	No information available	
Flash point	-3 °C / 27 °F	Setaflash Closed Cup
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	0.810 - 0.812	
Water solubility	Soluble in water	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other Information		
Softening point	No information available	
Molecular weight	No information available	
VOC Content (%)	89	
Density	0.806 - 0.808 g/cm3	
Bulk density	No information available	

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal use

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Excessive heat.

Incompatible materials

None known

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract. May be harmful if inhaled.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis.

Ingestion

Ingestion may cause irritation to mucous membranes. May be harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ETHANOL 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat)4 h
ACETONE 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m³(Rat)8 h
lsopropanol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m³(Rat)4 h

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Germ cell mutagenicity

No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Carcinogenicity Che

Chemical Name	ACGIH	IARC	NTP	OSHA
ETHANOL	A3	-	Known	Х
64-17-5				
Isopropanol	-	Group 3	-	Х
67-63-0				

ACGIH (American Conference of Governmental Industrial Hygienists) A2 - Suspected Human Carcinogen A3 - Animal Carcinogen IARC (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans Not classifiable as a human carcinogen NTP (National Toxicology Program) Known - Known Carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present May cause adverse effects on the bone marrow and blood-forming system. May cause **Chronic toxicity** adverse liver effects. Contains a known or suspected reproductive toxin. Blood, Central nervous system, Eyes, Liver, Reproductive System, Respiratory system, **Target Organ Effects** Skin. The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	9100 mg/kg
ATEmix (dermal)	27060 mg/kg
ATEmix (inhalation-dust/mist)	120.1 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

0.75 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

Disperses in water.

Chemical Name	Partition coefficient
ETHANOL 64-17-5	-0.32
ACETONE 67-64-1	-0.24

Isopropanol	0.05
67-63-0	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods	
Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations. Recover or recycle if possible. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated packaging	Do not reuse container.
US EPA Waste Number	D001, U002

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ETHANOL	Toxic
64-17-5	Ignitable
ACETONE	Ignitable
67-64-1	
Isopropanol	Toxic
67-63-0	Ignitable

14. TRANSPORT INFORMATION

DOT_ UN/ID No Proper shipping name: Hazard Class Packing Group	UN 1993 Flammable liquids, n.o.s, (Ethyl alcohol, isopropyl alcohol, acetone), Limited Quantity (LQ) 3 II
<u>IATA</u> UN/ID No Proper shipping name: Hazard Class Packing Group	UN 1993 Flammable liquid, n.o.s, (Ethyl alcohol, isopropyl alcohol, acetone), Limited Quantity (LQ) 3 II
IMDG UN/ID No Proper shipping name: Hazard Class Packing Group	UN 1993 Flammable liquids, n.o.s, (Ethyl alcohol, isopropyl alcohol, acetone), Limited Quantity (LQ) 3 II

15. REGULATORY INF	ORMATION	
International Inventories		
TSCA	Complies	
DSL/NDSL	Complies	
EINECS/ELINCS	Complies	
ENCS	Does not comply	
IECSC	Complies	
KECL	Complies	
PICCS	Complies	
AICS	Complies	
	I I	

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Isopropanol - 67-63-0	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

<u>CERCLA</u>

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE	5000 lb	-	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Ethanol is only considered a Proposition 65 developmental hazard when it is ingested as a alcoholic beverage.

Chemical Name	California Proposition 65	
ETHANOL - 64-17-5	Carcinogen	
	Developmental	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ETHANOL	Х	Х	Х
64-17-5			
ACETONE	Х	X	Х
67-64-1			
Isopropanol	Х	X	Х
67-63-0			
WATER	-	-	X
7732-18-5			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2A - Very toxic materials, B2 - Flammable liquid, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	-
HMIS	Health hazards 2	Flammability 3	Physical hazards 1	Personal protection B
	.			

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date	02-Oct-2018
Revision Note	

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

4

End of Safety Data Sheet